

# Prioritizing Life Safety While Addressing Classroom Security

Code-compliant  
product photos



## **Mechanical Classroom Security Lock**

Classroom security function locksets require a key to lock the outside lever from either side of the door, but allow free egress at all times without the use of a key.

Photo courtesy of Schlage Lock Company, LLC (part of Allegion plc)



## **Electrified Classroom Lock**

Electrified locks can be locked remotely, but are unlatched for egress by simply turning the inside lever.

Photo courtesy of Schlage Lock Company LLC (part of Allegion plc)



## **Panic Hardware Dogging Indicator**

An indicator on the classroom security lockset or panic hardware can help school staff members ensure that the door is locked to prevent access.

Photo courtesy of Von Duprin, LLC (part of Allegion plc)

Noncode-compliant  
conceptual images



## **Security Sleeve**

The model code requirements for classroom security do not allow locking methods to modify existing door closers or panic hardware.

Graphic images courtesy of Allegion



## **Security Bar**

Unlatching the door for egress must not require a key, tool, special knowledge or effort and operation of the hardware can not require tight grasping, pinching, or twisting of the wrist.

Graphic images courtesy of Allegion



## **Floor Lock**

Hardware used to unlatch the door must be mounted between 34 inches and 48 inches above the floor; hardware mounted above or below that range may not be accessible to all users.

Graphic images courtesy of Allegion



## **Auxiliary Lock**

Doors in a means of egress are required to unlatch with one operation; a separate deadbolt or auxiliary lock in addition to an existing latchset does not comply with the model codes.

Graphic images courtesy of Allegion